



800-523-3654

BALER & COMPACTOR

www.ptrco.com

Self-Contained Compactors



PT-301L

(30 Cubic Yards)

The PT-301L Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite*™ door seal.

Specifications

| | |
|---------------------------|-----------|
| Charge Box Capacity | 1.5 Cu Yd |
| Container Capacity | 30 Cu Yd |
| Clear Top Opening (L x W) | 36" x 60" |

Electrical Equipment

| | |
|-------------------------------|---------|
| Electrical Motor 208/230/460v | 3 Phase |
| Horse Power | 10 |
| Electrical Control Voltage | 120 VAC |

Performance Characteristics

| | |
|---------------------------|------------|
| Cycle Time | 33 sec |
| Total Normal Force | 39,265 lbs |
| Total Maximum Force | 47,000 lbs |
| Normal Ram Face Pressure | 21.8 psi |
| Maximum Ram Face Pressure | 26.2 psi |

Hydraulic Equipment

| | |
|-----------------------------|----------|
| Hydraulic Pump Capacity | 10.5 gpm |
| Normal Pressure | 2000 psi |
| Maximum Pressure | 2400 psi |
| Hydraulic Cylinder (2) Bore | 5" |
| Hydraulic Cylinder Rod | 3" |



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134
215-533-5100 • (FAX) 215-533-8907 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.
©PTR Baler & Compactor