

PTR

800-523-3654

BALER & COMPACTOR

www.ptrco.com

Self-Contained Compactors

Totally



Listed!

**PT-200**

(20 Cubic Yards)



The PT-200 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite*™ door seal.

Specifications

Charge Box Capacity	1 Cu Yd
Container Capacity	20 Cu Yd
Clear Top Opening (L x W)	31" x 50"

Electrical Equipment

Electrical Motor 208/230/460v	3 Phase
Horse Power	5
Electrical Control Voltage	120 VAC

Performance Characteristics

Cycle Time	45 sec
Total Normal Force	39,611 lbs
Total Maximum Force	52,287 lbs
Normal Ram Face Pressure	39.8 psi
Maximum Ram Face Pressure	52.6 psi

Hydraulic Equipment

Hydraulic Pump Capacity	6.5 gpm
Normal Pressure	1750 psi
Maximum Pressure	2400 psi
Hydraulic Cylinder (2) Bore	4"
Hydraulic Cylinder Rod	2.5"



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134
215-533-5100 • (FAX) 215-533-8907 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.
©PTR Baler & Compactor