

PTR

800-523-3654

BALER & COMPACTOR

www.ptrco.com

Self-Contained Compactors

PT-325

(25 Cubic Yards)

The PT-325 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite*™ door seal.

Specifications

Charge Box Capacity	2 Cu Yd
Container Capacity	25 Cu Yd
Clear Top Opening (L x W)	40" x 60"

Electrical Equipment

Electrical Motor 208/230/460v	3 Phase
Horse Power	10
Electrical Control Voltage	120 VAC

Performance Characteristics

Cycle Time	31 sec
Total Normal Force	42,708 lbs
Total Maximum Force	51,250 lbs
Normal Ram Face Pressure	23.8 psi
Maximum Ram Face Pressure	33.2 psi

Hydraulic Equipment

Hydraulic Pump Capacity	10.5 gpm
Normal Pressure	2000 psi
Maximum Pressure	2400 psi
Hydraulic Cylinder (2) Bore	4"
Hydraulic Cylinder Rod	2.5"



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134
215-533-5100 • (FAX) 215-533-8907 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.
©PTR Baler & Compactor