

**PTR**

800-523-3654

**BALER & COMPACTOR**

www.ptrco.com

**Self-Contained Compactors**

Totally



Listed!

# PT-330

(30 Cubic Yards)



The PT-330 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite*™ door seal.

### Specifications

Charge Box Capacity	1.5 Cu Yd
Container Capacity	30 Cu Yd
Clear Top Opening (L x W)	41" x 60"

### Electrical Equipment

Electrical Motor	208/230/460v	3 Phase
Horse Power		10
Electrical Control Voltage		120 VAC

### Performance Characteristics

Cycle Time	31 sec
Total Normal Force	42,708 lbs
Total Maximum Force	51,250 lbs
Normal Ram Face Pressure	35.7 psi
Maximum Ram Face Pressure	42.9 psi

### Hydraulic Equipment

Hydraulic Pump Capacity	10.5 gpm
Normal Pressure	2000 psi
Maximum Pressure	2400 psi
Hydraulic Cylinder (2) Bore	4"
Hydraulic Cylinder Rod	2.5"



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134  
215-533-5100 • (FAX) 215-533-8907 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.  
©PTR Baler & Compactor