

# BALER & COMPACTOR

## **Self-Contained Compactors**



### PT-100M thru PT350M

The PT-350 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite* <sup>TM</sup> door seal.

Normal Deck Height	46" [117 cm]	5" [13 cm]
Optional Deck Height	48" [122 cm]	7" [18 cm]
Optional Deck Height	47" [119 cm]	6" [15 cm]
Optional Deck Height	45" [114 cm]	4" [10 cm]

Capacity (Cu-Yd)	OVERALL LENGTH	CAN LENGTH	COMPACTOR HEIGHT
35 Cu-yd [27 cu-m]	296 1/2" [753 cm]	208" [528 cm]	101 1/2" [258cm]
30 Cu-yd [23 cu-m]	264" [671 cm]	175 1/2" [446 cm]	101 1/2" [258cm]
25 Cu-yd [19 cu-m]	235" [597 cm]	146 1/2" [372 cm]	101 1/2" [258cm]
20 Cu-yd [15 cu-m]	211" [536 cm]	122 1/2" [311 cm]	101 1/2" [258cm]
15 Cu-yd [11 cu-m]	182" [462 cm]	93 1/2" [237 cm]	101 1/2" [258cm]
12 Cu-yd [9 cu-m]	163" [414 cm]	74 1/2" [189 cm]	101 1/2" [258cm]
10 Cu-yd [8 cu-m]	150" [381 cm]	61 1/2" [156 cm]	101 1/2" [258cm]
	35 Cu-yd [27 cu-m] 30 Cu-yd [23 cu-m] 25 Cu-yd [19 cu-m] 20 Cu-yd [15 cu-m] 15 Cu-yd [11 cu-m] 12 Cu-yd [9 cu-m]	35 Cu-yd [27 cu-m] 296 1/2" [753 cm]   30 Cu-yd [23 cu-m] 264" [671 cm]   25 Cu-yd [19 cu-m] 235" [597 cm]   20 Cu-yd [15 cu-m] 211" [536 cm]   15 Cu-yd [11 cu-m] 182" [462 cm]   12 Cu-yd [9 cu-m] 163" [414 cm]	35 Cu-yd [27 cu-m]   296 1/2" [753 cm]   208" [528 cm]     30 Cu-yd [23 cu-m]   264" [671 cm]   175 1/2" [446 cm]     25 Cu-yd [19 cu-m]   235" [597 cm]   146 1/2" [372 cm]     20 Cu-yd [15 cu-m]   211" [536 cm]   122 1/2" [311 cm]     15 Cu-yd [11 cu-m]   182" [462 cm]   93 1/2" [237 cm]     12 Cu-yd [9 cu-m]   163" [414 cm]   74 1/2" [189 cm]

#### **Specifications**

Charge Box Capacity 3.5 Cu-YD [2.7 Cu-m] Clear Top Opening (L X W) 41" X 60" [104 cm x 152 cm] Capacity Per Hour 116 cy/hr

#### **Performance Characteristics**

Average Cycle Time 31 sec Total normal Force 42,708 lbs [189,974 N] Total Maximum Force 49,115 lbs [218,474 N] Normal Ram Pressure 28 psi [193 Kpa] Maximum Ram Pressure 33 psi [228 Kpa] Electric 208 / 230 / 460 - 3 Phase Control Voltage 110 - 120 Vac

#### **Hydraulic Equipment**

And the former that the former

Pump 10.50 GPM [39.7 L/m] Normal Pressure 2,000 psi [13,790 KPa] Maximum Pressure 2,300 psi [15,858 KPa] (2) Cylinder Bore 4" [10.2 cm] Cylinder Rod 2 1/2" [6.3 cm]



#### MADE IN AMERICA

PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134 215-533-5100 • (FAX) 215-533-8906 • 800-523-3654 • www.PTRCO.com