



Stationary Compactors





TP-2500HD

Tram-Pak Stationary Compactor

Designed For * Retailers * Hospitals * Hotels * Distribution Centers * * Manufacturing Centers * Recycling Centers * Home Centers *

Our TP-25HD00 compactor is designed for long lasting performance and durability. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. This unit has total U.L. approval, standard 3 button controls (On/Off key switch, mushroom stop, auto reverse) and a 13' Sealtite.

Specifications

Charge Box Capacity 2.5 Cu-YD [6.4 Cu-m] Clear Top Opening (L X W) 54 1/2" X 60" [138 cm x 152 cm] Capacity Per Hour 63 cy/hr

Performance Characteristics

Average Cycle Time 57 sec Total normal Force 59376 lbs 264,118 N Total Maximum Force 67,858 lbs [301,847 N] Normal Ram Pressure 33 psi [228 Kpa] Maximum Ram Pressure 38 psi [262 Kpa]

Electricrical Equipment

Electric 208 / 230 / 460 - 3 Phase Control Voltage 110 - 120 Vac

Hydraulic Equipment

Pump 15.0 GPM [56.8 L/m] Normal Pressure 1,800 psi [12,410 KPa] Maximum Pressure 2,100 psi [14,479 KPa] Cylinder Bore 6" [15.24 cm] Cylinder Rod 3 1/2" [8.9 cm] Weight 5,500 Lbs [2495 Kg]





MADE IN AMERICA

PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134 215-533-5100 • (FAX) 215-533-8906 • 800-523-3654 • www.PTRCO.com