

PTR

800-523-3654

BALER & COMPACTOR

www.ptrco.com

Stationary Compactors

Totally



Listed!



TP-3000HD

Our TP-3000HD compactor is designed for long lasting performance and durability. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. This unit has total U.L. approval, standard 3 button controls (On/Off key switch, mushroom stop, auto reverse) and a 13' Sealtite.

Specifications

Charge Box Capacity 3.22 Cu-YD [2.4 Cu-m]
Clear Top Opening (L X W) 68" X 60" [173 cm x 152 cm]
Capacity Per Hour 87 cy/hr

Performance Characteristics

Average Cycle Time 41 sec
Total normal Force 62,204 lbs [276,697 N]
Total Maximum Force 70,686 lbs [314,427 N]
Normal Ram Pressure 35 psi [241 Kpa]
Maximum Ram Pressure 39 psi [269 Kpa]

Electricrical Equipment

Electric 208 / 230 / 460 - 3 Phase
Control Voltage 110 - 120 Vac

Hydraulic Equipment

Pump 15.0 GPM [56.8 L/m]
Normal Pressure 2,200 psi [15,168 KPa]
Maximum Pressure 2,500 psi [17236 KPa]
Cylinder Bore 6" [15.24 cm]
Cylinder Rod 4" [10 cm]
Weight 6,850 Lbs [3,107 Kg]



MADE IN AMERICA

PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134
215-533-5100 • (FAX) 215-533-8906 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.
© PTR Baler & Compactor