PTR Baler and Compactor Company

Compactor Safety Checklist

2207 E. Ontario St. Philadelphia, PA 19134 1-800-523-1155 * (215)533-5100 FAX (215)537-8536

Compactor Safety Checklist

The following is a SAFETY CHECKLIST for the purpose of keeping the Compactor in a Safe Operating Condition.

A. Check that all signs and warnings are in place and in good condition:

| All access pannels must have a warning sign: | "CAUTION - DO NOT REMOVE ACCESS COVER EXCEPT FOR SERVICING. |
|--|--|
| All electrical devices such as contol cabinet, motor, etc., where voltage exceeds 120V must have warning: | TURN CONTROL PANEL KEYSWITCH TO 'OFF' POSITION & REMOVE KEY" "DANGER - HIGH VOLTAGE" |
| Near any opening where a person can enter or reach into: | "CAUTION - KEEP OUT" |
| Inside an area such as a hopper or chute: | "DANGER - DO NOT ENTER" |
| At all security doors: | "CAUTION - CLOSE SECURITY DOOR" |
| At all openings for feeding material: | "CAUTION - DO NOT OPERATRE COMPACTOR WHILE FEEDING" |
| B. Check the following contr | rol functions for proper operation: |
| On/Off Keyswitch | Man/Auto Selector Switch |
| For/Rev. Pushbutton Selector Switch | Cycle Start Button |
| Stop Button | Full Light |
| Other: | |
| C. Securit | y Door at Chute: |
| If compactor has a chute, the feeding opening must h compactor when the security door is open. | have a security door interlocked to stop operation of the |
| Chute has a security door | Chute door is a walk up style |
| Security door has electrical interlock | Security door has mechanical interlock |
| D Overall Safety Require | ements and Physical Appearance |
| Mainline disconnect switch must be located so that it | can be seen from the compaction end of the compactor. |
| Direct feeding compactor where the loading height is | less that 42 inchest must have: |
| (a) Deadman controls, with the control panel located loading zone pinchpoint area. | in such a way that the operator cannot reach the |
| of the body into the point of operation; in itself, stationary compactor parts; offer maximum visibility | of the point of operation consistent with other stationary compactor cannot be operated if the point |
| Compactor complies with above. | |
| Direct feed compactors having automatic cycling, must interlocked so that when the cover starts to open, th | |
| E. Clean up ar | rea around compactor |
| Pad Size & Condition Voltage | Hinge Size |
| Thru wall kit condition | Cylinder & Pin Size |
| Clean up of area is necessary | Condition of Chute |
| Condition of Hoses, especially by ground | Condition of Compactor, i.e. rust & paint |
| Serial No.: Serv | riceman's Signature: |
| | omer's Signature: |
| | :/ |