

BALER & COMPACTOR

www.ptrco.com

Self-Contained Compactors





PT-120

(12 Cubic Yards)



The PT-120 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a Sure-Tite TM door seal.

Specifications		Electrical Equipment	
Charge Box Capacity	1 Cu Yd	Electrical Motor 208/230/460v	3 Phase
Container Capacity	12 Cu Yd	Horse Power	5
Clear Top Opening (L x W)	31" x 50"	Electrical Control Voltage	120 VAC
Performance Characteristics		Hydraulic Equipment	
Performance Characteristics Cycle Time	45 sec	Hydraulic Equipment Hydraulic Pump Capacity	6.5 gpm
	45 sec 39,611 lbs		6.5 gpm 1750 psi
Cycle Time		Hydraulic Pump Capacity	

39.8

52.6

psi

psi



Normal Ram Face Pressure

Maximum Ram Face Pressure



Hydraulic Cylinder (2) Bore

Hydraulic Cylinder Rod





2.5"



