

BALER & COMPACTOR www.ptrco.com

Self-Contained Compactors



PT-235

(35 Cubic Yards)



Totally

The PT-235 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite* [™] door seal.

Specifications

Charge Box Capacity 1 Cu Yd Container Capacity 35 Cu Yd Clear Top Opening (L x W) 31" x 50"

Performance Characteristics

| Cycle Time | 29 sec | |
|---------------------------|--------|-----|
| Total Normal Force | 39,856 | lbs |
| Total Maximum Force | 52,611 | lbs |
| Normal Ram Face Pressure | 40.0 | psi |
| Maximum Ram Face Pressure | 52.9 | psi |

Electrical Equipment

Electrical Motor 208/230/460v Horse Power **Electrical Control Voltage**

3 Phase 10 120 VAC

INENI CO &WASTEC CANSI

Hydraulic Equipment

| Hydraulic Pump Capacity | 10.5 gpm |
|-----------------------------|----------|
| Normal Pressure | 2000 psi |
| Maximum Pressure | 2400 psi |
| Hydraulic Cylinder (2) Bore | 4" |
| Hydraulic Cylinder Rod | 2.5" |



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134 215-533-5100 • (FAX) 215-533-8907 • 800-523-3654 • www.PTRCO.com

Printed in the U.S.A ©PTR Baler & Compactor