

BALER & COMPACTOR

www.ptrco.com

Self-Contained Compactors



PT-330

(30 Cubic Yards)



The PT-330 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a Sure-Tite TM door seal.

Electrical Equipment

Hydraulic Cylinder (2) Bore

Hydraulic Cylinder Rod

Charge Box Capacity	1.5 Cu Yd	Electrical Motor 208/230/460v	3 Phase
Container Capacity	30 Cu Yd	Horse Power	10
Clear Top Opening (L x W)	41" x 60"	Electrical Control Voltage	120 VAC
Performance Characteristics		Hydraulic Equipment	
Cycle Time	31 sec	Hydraulic Pump Capacity	10.5 gpm
Total Normal Force	42,708 lbs	Normal Pressure	2000 psi
Total Maximum Force	51,250 lbs	Maximum Pressure	2400 psi
			-

35.7

42.9

psi

psi



Normal Ram Face Pressure

Maximum Ram Face Pressure

Specifications







4"

2.5"



