

BALER & COMPACTOR

www.ptrco.com

Self-Contained Compactors



PT-335

(35 Cubic Yards)



[22]

The PT-335 Compactor has been engineered and manufactured to provide many years of reliable service. The heavy-duty structural steel components are welded by AWS certified technicians and water tested to ensure leak proof containment under high compaction forces. This unit has total U.L. approval, standard 3 button controls, On/Off key switch, mushroom stop, auto reverse and a *Sure-Tite* TM door seal.

Electrical Equipment

Specifications		Electrical Equipment	
Charge Box Capacity	1.5 Cu Yd	Electrical Motor 208/230/460v	3 Phase
Container Capacity	35 Cu Yd	Horse Power	10
Clear Top Opening (L x W)	41" x 60"	Electrical Control Voltage	120 VAC
Performance Characteristics		Hydraulic Equipment	
Cycle Time	31 sec	Hydraulic Pump Capacity	10.5 gpm
Total Normal Force	42,708 lbs	Normal Pressure	2000 psi
Total Maximum Force	51,250 lbs	Maximum Pressure	2400 psi
Normal Ram Face Pressure	35.7 psi	Hydraulic Cylinder (2) Bore	4"
Maximum Ram Face Pressure	42.9 psi	Hydraulic Cylinder Rod	2.5"



Specifications









