

BALER & COMPACTOR

www.ptrco.com

Stationary Compactors





TP-750

Tram-Pak **Stationary Compactor**

Designed For

- * Retailers * Hospitals * Hotels *
- * Recycling Centers * Home Centers *

The TP-750 was specially designed for applications with space constrictions. It utilizes a .75 cubic yard compactor that attaches to either a 6 or 8 Yard Rear or Front Load container. Its 4 inch cylinder produces over 20,000 lbs of normal force. It is a powerful force for your tight space applications. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. This unit has total U.L. approval, standard 3 button controls (On/Off key switch, mushroom stop, auto reverse) and a 13' Sealtite.

Specifications		Electrical Equipment	
Charge Box Capacity	.75 Cu Yd	Electrical Motor 208 / 230 / 460	3 Phase
Clear Top Opening (L x W)	36" x 37"	Electrical Control Voltage	120 VAC
Capacity Per Hour	58.7 cy/hr		
		Hydraulic Equipment	
Performance Characteristics		Hydraulic Pump Capacity	6.5 gpm
Cycle Time	36.8 sec	Normal Pressure	1600 psi
Total Normal Force	20,000 lbs	Maximum Pressure	2000 psi
Total Maximum Force	25,000 lbs	Hydraulic Cylinder	4" Bore
Normal Ram Face Pressure	27.2 psi	Hydraulic Cylinder	2.5" Rod
Maximum Ram Face Pressure	34 psi	Weight	3,500 lbs













